## **Strand Pendant Lamp**

"The Strand Pendant Lamp is formed from a sprayed cocoon material with its cloud-like appearance that tightly clings to a spinning steel frame. It consists of tiny strands for a complex, intriguing structure that shrouds the light source while acting as its diffuser. With its see-through expression, the cocoon material allows for the Strand Pendant Lamp to filter light for a warm, comfortable glow."

- Benjamin Hubert



| Designed by            | Benjamin Hubert / 2019  |  |  |
|------------------------|---|--|--|
| Environment            | Indoor  |  |  |
| Country of Production  | Italy   |  |  |
| Preassembled           | Yes.  |  |  |
| Description            | The Strand Pendant Lamp is designed with soft, playful forms for a modern expression. The design<br>provides both diffused lighting and direct lighting, the latter through its top and bottom opening.<br>The design is made in a sprayed cocoon material that consists of tiny strands for a complex,<br>intriguing structure that, paired with its modern form, gives the Strand Pendant Lamp an almost<br>cloud-like appearance. With its cocoon material filtering light through for a warm, comfortable<br>glow, the Strand Pendant Lamp hovers lightly in space, bringing comfort, harmony and a refined<br>sensitivity to any room. |  |  |
| Material               | The Strand Pendant Lamp is made of a cocoon layer with an inner steel structure, a PVC cord and PVC covered steel wire.   |  |  |
| Cleaning $\delta$ Care | Clean with soft dry cloth only. Always switch off the electricity supply before cleaning.   |  |  |
| Cord length            | 300, 500 cm / 118.1", 196.9"  |  |  |
| Light source included  | Closed - 17.7", Closed - 23.5", Closed - 31.5", Open - 11", Open - 16", Open - 23.5": No  |  |  |
| Ceiling Cap included   | Closed - 17.7", Closed - 23.5", Closed - 31.5", Open - 11", Open - 16", Open - 23.5": Yes   |  |  |
| Dimmable function      | Yes.  |  |  |
| Additional information | Please note that the Open Ø60, Closed Ø45, Ø60 and Ø80 come with a wire suspension system with three metal wires. Metal wires 490 cm. Cord length 500 cm. Total possible suspension length from ceiling 480 cm.   |  |  |



## **Strand Pendant Lamp**

Dimensions

### Closed - 23.5" Length:

Height:

Width:

Diameter:

Cord Length:

Closed - 31.5"

Length:

Height: Width:

Diameter:

Cord Length:

Closed - 17.7"

Length: Height:

Width:

Diameter: Cord Length:

Open - 23.5" Length:

Cord Length:

Height:

Width Diameter:

Open - II" Length:

Height: Width:

Diameter:

Open - 16"

Length:

Height: Width:

Diameter:

Cord Length:

Cord Length:

60 cm / 23.6" 54,8 cm / 21.6" 60 cm / 23.6" 60 cm / 23.6" 500 cm / 196.9"

80 cm / 23.9"

80 cm / 23.9" 80 cm / 31.5"

60,8 cm / 23.9"

500 cm / 196.9"

45 cm / 17.7"

45 cm / 17.7" 45 cm / 17.7"

36,4 cm / 14.3"

500 cm / 196.9"

60 cm / 23.6" 40,3 cm / 15.9"

60 cm / 23.6"

60 cm / 23.6"

500 cm / 196.9"







28 cm / 11" 37,4 cm / 14.7" 28 cm / 11" 28 cm / 11" 300 cm / 118.1"

40 cm / 15.7" 50,2 cm / 19.8" 40 cm / 15.7" 40 cm / 15.7" 300 cm / 118.1"



# Ready-to-ship

White - Open White - Closed

Lamp rating

Voltage Frequency IP Rating Socket

Socket

Closed - 23.5"

### 120V 60Hz IP20

120V 60Hz IP20 1 x E26 Max. 60W Max. 1 x E26 Max. 60W Max. 30W CLFMax. 25W LED 30W CLF Max. 25W LED 30W CLF Max. 25W LED 30W CLF Max. 25W LED

Open - II" Voltage 120V Frequency 60Hz IP Rating IP20

Open - 16" 120V 60Hz IP20 1 x E26 Max. 40W Max. 1 x E26 Max. 40W Max. 13W CLF Max. 13W LED 13W CLF Max. 13W LED

Closed - 31.5"

Closed - 17.7" 1 x E26 Max. 60W Max.

120V

60Hz

IP20

Open - 23.5" 120V 60Hz IP20

1 x E26 Max. 60W Max.

## **Strand Pendant Lamp**

#### Light source recommendation

| Closed - 93.5"    | Closed - 31.5"   | Closed - 17.7"  | Open - 23.5"   |
|-------------------|--|---|--|
| E26               | E26  | E26   | E26  |
| Ø125 x 175 mm     | Ø125 x 175 mm  | Ø125 x 175 mm   | Ø125 x 175 mm  |
| <b>ъре</b> G125   | G125   | G125  | G125   |
| e LED             | LED  | LED   | LED  |
| Max. 60W Max. 30' | Max. 60W Max. 30W CLF Max. 60W Max. 30W  |   | Max. 60WMax. 30W   |
| Max. 25W LED      | CLFMax. 25W LED  | CLFMax. 25W LED   | CLFMax. 25W LED  |
| Open - II"        | Open - 16"   |   |  |
| E26               | E26  |   |  |
| Ø80 x 115 mm      | Ø80 x 115 mm   |   |  |
| ape G80           | G80  |   |  |
| e LED             | LED  |   |  |
| Max. 40WMax. 13W  | W Max. 40WMax. 13W   |   |  |
| CLFMax. 13W LEI   | O CLFMax. 13W LED  |   |  |
|                   | Ø125 x 175 mm     ope   G125     LED   Max. 60W Max. 30     Max. 25W LED   Ø125     Open - II"   E26     Ø80 x 115 mm   Ø80     Open   LED     Max. 40WMax. 13V   Max. 40WMax. 13V | E26   E26     Ø125 x 175 mm   Ø125 x 175 mm     ope   G125   G125     LED   LED     Max. 60W Max. 30W CLF Max. 60WMax. 30W     Max. 25W LED   CLFMax. 25W LED     Open - II"   Open - I6"     E26   E26     Ø80 x 115 mm   Ø80 x 115 mm     ope   LED     LED   LED     Max. 40WMax. 13W   Max. 40WMax. 13W | E26 E26 E26 E26   Ø125 x 175 mm Ø125 x 175 mm Ø125 x 175 mm   Ope G125 G125 G125   Ax 60W Max. 30W CLF Max. 60WMax. 30W Max. 60WMax. 30W   Max. 60W Max. 30W CLF Max. 60WMax. 30W Max. 60WMax. 30W   Max. 25W LED CLFMax. 25W LED CLFMax. 25W LED   Open - II" Open - I6"   E26 E26   Ø80 x 115 mm Ø80 x 115 mm   open LED   Max. 40WMax. 13W Max. 40WMax. 13W |







