Under The Bell Pendant Lamp

"Under The Bell is more than just a lampshade—when situated over a table or in an open space, the bell-shaped light creates its own space within the environment. As such, the design embraces and shelters the people underneath, both in a physical and abstract manner, for an intimate atmosphere. The design is made using fibers from recycled plastic bottles that, along with its unique shape, enables Under The Bell to absorb sound and improve the acoustics of any room."



Iskos-Berlin

Designed by Iskos-Berlin / 2011

About the designer Iskos-Berlin is a Copenhagen-based design duo that has made international headlines within

furniture, industrial and graphic design. The studio, formerly known as Komplot Design has collaborated with some of the world's most prestigious manufacturers and their furniture, lighting and other design products are exhibited at numerous design museums around the world including

MoMA and the Designmuseum Denmark.

Environment Indoor

Country of Production Germany

Preassembled Yes.

Description Designed in a material that uses up to 41% fibers from recycled plastic bottles, the Under The Bell

Pendant Lamp not only brings a tactile and modern expression to any space but also impacts the acoustics of a room through its soft shade, paired with its graphic lines and subtle color palette

Material Shade made using up to 41% fibers from recycled plastic bottles. Rubber cord.

Cleaning & Care

Vacuum to remove dust. Clean off any marks with a clean moist cloth. Always switch off the

electricity supply before cleaning.

Cord length 500 cm / 196.9"

Dimmable function Yes.



Under The Bell Pendant Lamp



Dimensions

Ø 21.7"

Length: 55 cm / 21.7" Height: 31 cm / 12.2" Width: 55 cm / 21.7" 55 cm / 21.7" Diameter: Cord Length: 500 cm / 196.9"



Ø 32.25"

82 cm / 32.3" Length: Height: 46 cm / 18.1" Width: 82 cm / 32.3" 82 cm / 32.25" Diameter: Cord Length: 500 cm / 196.9"



Ready-to-ship

Black Grey

White Mélange



Lamp rating

Ø 32.25" Voltage 120V 120V 60Hz 60Hz Frequency IP Rating IP20 IP20

Socket 1 x E26 Max. 30W; self- 1 x E26 Max. 30W; selfballasted CFL Max. 60W; ballasted CFL Max. 60W; Incandescent, Type A Incandescent, Type A

Max. 11W; Self-ballasted Max. 11W; Self-ballasted LED

LED

Light source recommendation

Ø 21.7" Ø 32.25" Lamp Base E26 E26 Ø125 x 175 mm Dimensions Ø125 x 175 mm **Light Source Shape** G125 G125 Light Source Type LED LED

Max Voltage Max. 30W; self-ballasted Max. 30W; self-ballasted

CFL CFL

Max. 60W; Incandescent, Max. 60W; Incandescent,

Type A Type A

Tests, Labels δ Certifications

Safety & Regulations

cETLus or cULus





















